

[Home](#) ■ [Lösningar](#) ■ [Energieffektivitet](#) ■ [Sludge Treatment](#) ■ [Screening](#)

Energy-Efficient Sludge Screening





Sludge screening is recommended where:

- screens in the headworks are not fine enough,
- sludge, e.g. septic sludge, is imported,
- clogging of sludge treatment components, e.g. heat exchangers, must be prevented,
- certain solids could impair treatment or reuse of treated sludge.

Our ROTAMAT® Sludge Screen Ro 3.1 has a bar spacing of 6 or 8 mm. Sludge, e.g. imported septic sludge, flows through the screen by gravity. Removed screenings are washed and compacted to 30 – 45 %DS. Power consumption is 10 – 20 Wh/m³.

Sludge is pumped through perforations of our [STRAINPRESS® Sludgecleaner](#). Their diameter is 3 – 10 mm, most commonly 5 mm. The Strainpress also removes hair and fibres and compacts the screenings to 35 – 45 %DS. Its power consumption, including pumping, is around 50 Wh/m³.

A member of the HUBER Group

Postadress / Mailing address:
HUBER Technology Nordic AB
Box 125, 437 22 Lindome, Sweden

Besöksadress / Visiting address: Telephone: + 46 31 99 64 60
Heljesvägen 4
437 36 Lindome, Sweden

E-mail: info@hubersverige.se

www.hubersverige.se
Bankgiro: 5870-0386
Postgiro: 6402198-3