

The HUBER Washing Drum separates the coarse material > 10 mm from the material to be treated. Depending on the nature of the raw material the fraction of the coarse material differs regarding composition and quantity. In case the treatment of coarse material has to be continued for better disposal it is possible to add coarse material washing as further process step to the [RoSF5 grit treatment process](#).

With the help of the Coarse Material Washer the coarse material is separated into the "gravel" fraction and the "organics" fraction (leaves, twigs etc.). The coarse material is separated into light and heavy material fractions by using wash water and air. The circulating water pipe supplies the water required so that no additional water is necessary.

- separation of the mineral and organic fractions
- loss on ignition of the mineral fraction < 5 %
- organic fraction can be composted
- reduction of disposal costs
- sturdy stainless steel make
- manual control of water- and air additions possible

► [HUBER Rotamat Tvättrumma RoSF9](#)

- First complete treatment plant for sewer grit installed in China

A member of the HUBER Group

Postadress / Mailing address:
HUBER Technology Nordic AB
Box 125, 437 22 Lindome, Sweden

Besöksadress / Visiting address: Telephone: + 46 31 99 64 60
Heljesvägen 4
437 36 Lindome, Sweden

E-mail: info@hubersverige.se

www.hubersverige.se
Bankgiro: 5870-0386
Postgiro: 6402198-3